

A5+

Integrated Amplifier with Bluetooth and Auracast



The ARCAM A5+ is for sharing intimate listening experiences with family and friends.

The “A” in ARCAM stands for amplification, where our expertise lies. The A5+ is the latest in nearly 50 years of amplifier design and manufacture, dating back to our first product in 1976—the A&R Cambridge A60 amplifier. Since the launch of the award-winning ARCAM Radia A5, we haven’t rested. Our engineering team pushed further to create the ARCAM A5+, an even better sounding and more versatile integrated amplifier.

The A5+ features an enhanced power supply design and cutting-edge wireless capabilities straight out of the box. Snapdragon Sound delivers uncompressed digital audio via Bluetooth, while Auracast enables multiple compatible headphones or speakers to share music wirelessly, with no pairing required.

With a wide array of digital and analogue inputs, including a meticulously tuned phono stage, the A5+ ensures impeccable sound quality for everything from vinyl to streaming.

Features

- Wireless audio with Bluetooth 5.4
- Featuring Snapdragon Sound for wireless lossless audio
- Featuring Auracast for connecting wireless headphones or speakers to play music in multiple spaces.
- Hi-res audio digital inputs
- ESS ES9018 DAC
- Meticulously tuned phono stage
- Class AB amplification
- 2x 50 Watts (8Ω) Power Output
- Compact remote control
- Solid aluminium dials
- Aluminium front, top, sides and rear panels
- Plastic free packaging



Continuous power output (0.5% THD) 2 channels driven	
8Ω, 20Hz - 20kHz	50W
4Ω, 1kHz,	75W
Harmonic distortion, 80% power, 8Ω at 1kHz	0.003%
Analogue Inputs	
Number of inputs	3 (RCA pairs)
Signal/noise ratio (A-wtd, ref. 50W, 1V input)	106dB
Frequency response	20Hz—20kHz ± 0.2dB
Phono (MM) Input	
Input impedance	47kΩ + 100pF
Frequency response (ref. RIAA curve)	20Hz—20kHz ± 1dB
Digital Inputs	
Supported Sample Rates (kHz)	192, 176.4, 96, 88.2, 48, 44.1
Bit depths (bit)	24, 16
Frequency response (filter 1)	20Hz—20kHz ± 0.2dB
Signal/noise ratio (A-wtd, ref. 50W, 0dBFS)	109dB
Headphone Output	
Maximum output level (RMS) into 32Ω/300Ω	2.5V/5V
Load range	16Ω - 2kΩ
Wireless Specifications	
Bluetooth Version	5.4; A2DP Sink/Source, AVRCP, BLE, Snapdragon Sound, AAC, LE Audio, Auracast
Bluetooth Transmitter Frequency and Power	2,400 MHz to 2,483.5 MHz: <20dBm
General	
Mains voltage	100V or 110–120V or 220–240V, 50–60Hz
Power consumption (maximum)	350W
Power consumption (standby)	<0.5W
Dimensions W x D (including speaker terminals) x H (including feet)	431 x 344 x 83mm
Weight (net)	8.14 kg
Weight (packed)	11.36kg
Supplied accessories	Mains lead(s) Remote control with 2 x AAA batteries Quick Start Guide Important Safety Instructions