

CD25



Compact Disc Player

ARCAM celebrates its enduring commitment to Compact Disc with the CD25, a high-performance CD player designed to bring every album closer to the listener. Building on a heritage that began with the Delta 70 in 1986, the CD25 distils decades of digital expertise into a modern, musically engaging design.

Created through inquisitive engineering and a deep passion for music, the CD25 is developed using objective measurement and extensive blind listening tests to ensure performance that is both technically precise and emotionally compelling.

At its core is an all-new dual-mono DAC design, combined with a low-noise linear power supply and a vibration-damped disc mechanism. Together, these elements deliver exceptional detail, dynamics, and clarity, reaffirming the musical relevance of Compact Disc in a modern hi-fi system.

The CD25 stands as the finest CD player ARCAM has ever produced — a perfect partner for the Radia Series and a celebration of physical music, brought vividly to life.

Features

- Dual-Mono DAC Architecture delivers superior channel separation, lower noise, and a more precise, spacious stereo image.
- Low-Noise Linear Power Supply provides a stable, ultra-quiet electrical foundation, allowing fine musical detail and dynamic contrast to emerge clearly.
- Vibration-Damped Disc Mechanism minimises mechanical interference for improving timing accuracy, clarity, and overall musical coherence.
- Balanced and RCA Analogue Outputs ensures optimal system matching with Radia Series amplifiers and others.
- ARCAM-Tuned via Blind Listening Tests combines objective accuracy with musical engagement, ensuring sound quality that is both technically precise and emotionally involving.
- Plastic free packaging for easy disposal or natural materials



Playback		
Supported Media	CD (Audio), CD-R (Audio / Data), CD-RW (Audio / Data)	
Supported files (Data)	WAV (LPCM), FLAC, MP3, AAC	
Supported Sampling Rates	WAV/FLAC	96, 88.2, 48, 44.1, 32 kHz
	MP3/AAC	48, 44.1, 32 kHz
Supported Bit depth	16-24 bit	
Outputs		
Analogue Outputs	2 (1 RCA Pair, 1 XLR Pair)	
Maximum Analogue Output (0dBFS, RCA/XLR)	2.2/4.4VRMS	
Signal/Noise ratio (A-wtd, ref. 16-bit/24-bit, 0dBFS)	93dB/115dB	
Frequency Response (filter 1)	20 Hz – 20 kHz ±0.1 dB	
Digital Outputs	2 (1 Optical, 1 Coaxial)	
General		
Mains Voltage	100–120V or 220–240V, 50/60 Hz	
Maximum power consumption	20 W	
Standby power consumption	<0.5 W	
Maximum ambient operating temperature	35°C/95°F	
Dimensions W x D (including speaker terminals) x H (including feet)	431 x 329 x 84 mm	
Weight (net)	6.5 kg	
Weight (gross)	9.5 kg	
Supplied accessories	Mains lead(s)	
	Remote control with 2 x AAA batteries	
	Quick Start Guide	
	Important Safety Instructions	